



myLittleAdmin for MS SQL Server

Silent Logon Module

version 3.5

The silent logon module allows integrating myLittleAdmin into existing control panels without the need for the user to enter his connection login/password twice.

Control panel must send **silentlogon.aspx** page several values (login, password and optional ones) using the **POST** method.

| Value | Description |
|-----------------------|--|
| Login | <p>The login to connect with. This value cannot be empty. If this value is not defined, then the silent logon fails and the default connection page is automatically displayed.</p> <p><u>Example:</u> <ul style="list-style-type: none"> ➔ mla_user13 </p> |
| Password | <p>The password of the login. This value cannot be empty. If a wrong password is sent, then the silent logon fails and the default connection page is automatically displayed.</p> <p><u>Example:</u> <ul style="list-style-type: none"> ➔ x124Pojoy7 </p> |
| ServerName | <p>The name of the server (or instance) to be connected. If this value is not defined, then the first server defined in the config.xml file will be used.</p> <p>If this value is set, then it must have been defined in the config.xml file too (unless you have an "unlimited server" license). Else the first server defined in the config.xml file will be used.</p> <p><u>Example:</u> <ul style="list-style-type: none"> ➔ MLTSRV\SQL2K5 ➔ MLTSRV ➔ 10.0.0.45 </p> |
| InitialCatalog | <p>The name of the database to be managed.</p> <p>If this value is set, then myLittleAdmin will only allow managing the specified database. If this value is not set, then myLittleAdmin will allow managing all databases the user has an account for.</p> <p>If the SQL Server contains an important count of databases, it is highly recommended to set this value.</p> <p><u>Example:</u> <ul style="list-style-type: none"> ➔ db120522 </p> |

| | |
|--------------------------|---|
| Protocol | <p>The network protocol to be used. If this value is not defined, then the default value defined in the config.xml file will be used</p> <p><u>Allowed values:</u></p> <ul style="list-style-type: none">➔ dbmssocn➔ dbnmpntw➔ dbmsrpcn➔ dbmsadsn➔ dbmsgnet➔ dbmslpcn➔ dbmsspxn |
| PacketSize | <p>The packet size (in bytes) to be used. If this value is not defined, then the default value defined in the config.xml file will be used.</p> <p><u>Example:</u></p> <ul style="list-style-type: none">➔ 4096 |
| ConnectionTimeout | <p>The time-out value for a connection in seconds. If this value is not defined, then the default value defined in the config.xml file will be used.</p> <p><u>Example:</u></p> <ul style="list-style-type: none">➔ 15 |
| ExecutionTimeout | <p>The time-out value for an execution in seconds. If this value is not defined, then the default value defined in the config.xml file will be used.</p> <p><u>Example:</u></p> <ul style="list-style-type: none">➔ 0 |